

**Local Race City/Region:****Stock Champ's Name** _____**AASBD
Car Number**

Inspection Area	Description	Photos	Pass?
Steering Stop Installation	Steering stop hardware per plans	Photo 1.3	_____
Foot Brace Installation	Foot brace hardware per plans	Photo 2.5	_____
Kingpin Installation	Bushing installed per plans	Photo 3.5 & 3.7	_____
	Front kingpin washer stack per plans	Photo 3.20	_____
	Rear kingpin washer stack per plans	Photo 3.19	_____
Steering Hardware Installation	Steering hardware per plans	Photos 4.6, 4.16, & 4.10(a) & (b)	_____
	Cable pulleys installed per plans	Photos 4.10(a) & (b)	_____
Steering Cabling Installation	Cable pulley hardware per plans	Photo 5.6	_____
	Axle eyebolt per plans	Photo 5.13	_____
	Steering cable adjusters per plans	Photos 5.18 & 5.32	_____
	Steering cable routing per plans	Photos 5.24, 5.27, 5.38(a) & (b)	_____
	Cable double-clamped per plans	Photo 5.37	_____
Stabilizer Installation	Bushing installed per plans	Photos 6.5 & 6.7	_____
	Stock radius rod assembly per plans	Photos 6.16, 6.19, 6.23 & 6.26	_____
Brake Pad Installation	Brake pad installed per plans	Photos 7.1 & 7.4	_____
	New brake pad installed	_____	_____
Brake Installation	Brake pedal hardware per plans	Photos 8.4, 8.12 & 8.18	_____
	Cable pulley installed per plans	Photo 8.24	_____
	Brake plunger installed per plans	Photos 8.26 & 8.30	_____
	Awning pulley hardware per plans	Photo 8.41	_____
	Cable double-clamped per plans	Photo 8.45	_____
	Brake cable routing per plans	Photos 8.47 & 8.50	_____
Weight Bolt Installation	Adjustable weight hardware per plans	Photo 9.10	_____
	Fixed weight hardware per plans	Photo TT 1.11	_____
	Ten pounds of adjustable weight with wing nut	_____	_____
Airfoil Installation	Front axle plastic airfoils installed per plans	Photos 10.1 & 10.3	_____
	Rear axle plastic airfoils installed per plans	Photos 10.7 & 10.9	_____
Shell Installation	Front foam installed per plans	Photo 12.4	_____
	Optional rear and side foam installed per plans	Photo TT 3.10	_____
	Screw in nose of the shell	Photo 12.11	_____
	Shell flush with bottom of floorboard	_____	_____
	Shell circumference of 39-1/2 inches	_____	_____
	Shell rear lip minimum of 3/4 inches	Figure TT 3.10	_____
Signage, Lettering & Decoration	Shell decals and decorations per plans	Photo 13.1 (all views)	_____
	All-American Soap Box Derby Number	Photo 13.1 (all views)	_____
	Title/National Sponsor(s)	Photo 13.1 (all views)	_____
	Local Race City Organization OR Rally Region	Photo 13.1 (all views)	_____
	All-American Soap Box Derby Logo	Photo 13.1 (all views)	_____
Floorboard	Coatings with tung oil and/or wax	_____	_____
Axles	2000 or newer. 7-15/16" maximum nose to 61-1/8" inches kp center to kp center +/- 1/16	Kingpin center	_____
Errors in Construction	Repairs must be completed within one hour	_____	_____

There may be other items or areas on the car inspected that do not show up on this inspection sheet.

The persons signing this document acknowledge that, as a condition precedent to participation in the All-American Soap Box Derby (AASBD) World Championship in Akron, Ohio, the cars of such winner must pass an inspection conducted in Akron, Ohio by the AASBD representatives chosen by and in the sole and absolute discretion of the AASBD. The inspection shall be conducted by the AASBD in accordance with the applicable rules, spirit, plans and specifications as the AASBD shall determine and it is understood and agreed that the decision of the AASBD regarding compliance with these items as well as qualification/disqualification of any car shall be final and binding upon all parties.

Local Race Director Signature

Date

Regional Director Signature

Date